

DECT handset I766

Robust DECT handset for voice and messaging in demanding environments



The I766 DECT handset is a powerful communication tool and with its ruggedized design ideal for the most demanding environments such as in healthcare, manufacturing and industry.

- Provides many call control features seamlessly integrated with the PBX
- Any place accessibility, improving customer satisfaction, while users keep full control over their presence
- Valuable unified communications, including central directory access, presence and extensive messaging and alarming features
- Additional protection with the man-down function, SOS alarm key, pull cord and location detection
- Intuitive user interface with colour display and icon-based menus
- Dual- and rack chargers; also charging additional batteries
- Bluetooth headset connectivity provides freedom, comfort and flexibility
- DECT compliance for high quality speech and security
- High definition audio in line with CAT-iq



At a Glance

- Very sturdy, yet appealing design
- Large 2.4-inch, high resolution display
- High definition audio in line with CAT-iq incl. loudspeaking mode
- Top SOS button, man-down and pull cord alarm
- Vibrator
- Micro USB, MicroSD card
- Bluetooth (also BTLE)
- Desk- and rack chargers
- RTLS (Real-time Location System) via DECT signal strength and beacons
- IP65 dust and water protection
- For NEC DECT and IP DECT



Features

Call handling¹⁾	<ul style="list-style-type: none"> • Automatic call answer • Caller log • CLI (name and number support) • Last number redial • Recall/hold (enquiry) • Standby time up to 160 hours 	<ul style="list-style-type: none"> • Call reject option • HD audio and seamless handover • On-hook number preparation • Silent Charging • Talk time up to 16 hours
Design	<ul style="list-style-type: none"> • Robust design for use in professional and industrial environments • LED indication (4 colours) for e.g. missed call and MWI 	<ul style="list-style-type: none"> • Ambient noise reduction • Dust and water resistance: IP65 • HAC compliant
Directory	<ul style="list-style-type: none"> • Corporate directory 	<ul style="list-style-type: none"> • Personal phone book with multiple numbers per contact
Display	<ul style="list-style-type: none"> • Color graphic 2.4" TFT display, 240 x 320 pixels (256K) compliant • Illuminate display: on incoming calls and message • Power saving mode: display dim lit or completely off 	<ul style="list-style-type: none"> • Date & time indication: synchronized with PBX clock • Character set: WideChar (UTF160) • LCD Backlit
Headset	<ul style="list-style-type: none"> • Wired headset support (3.5 mm) 	<ul style="list-style-type: none"> • Bluetooth headset
Keys	<ul style="list-style-type: none"> • 12 keypad keys (0..9, *, #) with text mode support • 4 function keys for speed dialling and menu shortcuts • Recall (enquiry) key combined with on-hook key • Menu navigation keys: up, down, left and right and OK • Distinctive SOS alarm key • Keypad backlit • Key lock key 	<ul style="list-style-type: none"> • On- and off-hook: 2 separate keys • Power on/off key combined with off-hook key • Soft keys: 3, menu dependent function • Increase and decrease volume • Menu key • Speakerphone key
Localization	<ul style="list-style-type: none"> • Supported languages: 14 • Triple frequency band 	<ul style="list-style-type: none"> • Multiple (RF) power levels
Memory card (optional)	<ul style="list-style-type: none"> • Storage of configuration and subscription data, personal phone book and caller filter • Easy subscription to another handset by transferring the memory card 	<ul style="list-style-type: none"> • Blocking of changes to the configuration settings • Easy (pre-)installation by programming the memory card • Memory card type: MicroSD
Menu	<ul style="list-style-type: none"> • Easy menu programming 	
Messaging	<ul style="list-style-type: none"> • Messaging (LRMS) support • Support of different urgencies/priorities: Normal, urgent and emergency 	<ul style="list-style-type: none"> • Message waiting (voicemail) • Message broadcast support • Set-up of voice call to call back number in message
Mobility	<ul style="list-style-type: none"> • Antenna diversity 	<ul style="list-style-type: none"> • Multiple subscriptions DECT systems: 10
Other features	<ul style="list-style-type: none"> • Automatic key lock • Man down detection: detection of non-vertical position leads to dialling a programmed destination or to sending an alarm message 	<ul style="list-style-type: none"> • Optional RFID module (DLA) for location detection • Accessory features: Calculator, stopwatch and alarm clock • Pull cord for personal safety support
Sound/Audio	<ul style="list-style-type: none"> • Adjustable ringer volume • Loudspeaker mode/hands free • Trembler 	<ul style="list-style-type: none"> • Adjustable earpiece/loudspeaker volume • Microphone mute • Silent ring support
Security	<ul style="list-style-type: none"> • Automatic encryption for secure calls 	
Service/Maintenance	<ul style="list-style-type: none"> • Software upgrading via air interface ²⁾ • Software upgrading via USB interface 	<ul style="list-style-type: none"> • Backup of local data via memory card
User data	<ul style="list-style-type: none"> • Internal memory for storage of configuration data, personal phone book, messages, caller log, caller filter and calendar entries 	<ul style="list-style-type: none"> • Optional memory card
User interface	<ul style="list-style-type: none"> • Icon driven menu • Configurable LED (4 colours) indicator, e.g., for missed call and message waiting • Ringer tones/melodies: 20 • Selectable display background 	<ul style="list-style-type: none"> • Status line indicators in the display • Distinctive melodies for external and internal calls, messages and priorities and per contact in the local phone book • Audible indicators are user selectable

1) Features depend on the capabilities of the PBX and the DECT system used

2) Needs to be supported by the DECT system

Physical Characteristics

Dimensions	<ul style="list-style-type: none"> Handset: 145 x 55 x 24 mm Charger: 77 x 77 x 61 mm Charger Rack: 462 x 77 x 61 mm
Weight	<ul style="list-style-type: none"> Handset: 123 g Charger: 78 g AC Adapter: 25 g
Protection	<ul style="list-style-type: none"> Handset: IP65
Range	<ul style="list-style-type: none"> Indoor: 50 m max ³⁾ Outdoor: 300 m max ³⁾
Power Supply	<ul style="list-style-type: none"> Handset: 3.7V, 1100mAh Lithium-ion battery Chargers - (EU mains plug, USB output / multi-region mains plug, USB output): <ul style="list-style-type: none"> - Input: 100-240VAC/50/60Hz/250mA - Output: 5VDC/1000mA Charger rack (multi region mains plug, 5 mm DC plug)
Colour and Finishing I766	<ul style="list-style-type: none"> Handset: Black/Grey Desktop charger: Black Charger rack: Black
Audible indicators	Selectable audible indicators: <ul style="list-style-type: none"> Key click Charger warning Coverage warning Confirmation tone
Status line indicators	Status line indicators in the display are: <ul style="list-style-type: none"> Battery condition Message waiting Caller filter active Microphone mute Field strength Missed call Key lock active Ringer off Loudspeaker active
LED indicators	Four of the following user selectable indicators can be assigned to the indicator LED: <ul style="list-style-type: none"> Battery low Bluetooth Charging Text message Silent Charging Text or voice message Missed call Voice message
Supported menu languages	The handset supports 14 selectable languages: Danish, Dutch, English, French, German, Greek, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
<p>3) The radio coverage of DECT handsets depends on the environment and the presence of obstacles</p> <p>4) The mains plug contains a changeable part for the different power plugs</p>	

Accessories

I766 handset accessories	<ul style="list-style-type: none"> Swivel Belt Clip Set Spring Belt Clip Set Battery pack Desktop Charger with adapter Charger rack (6 handsets) with AC Adapter Bluetooth headset Wired headset DLA locator unit MicroSD memory card
---------------------------------	--

Transmission & Frequency

Transmitted radio RF power	Less than 250 mW ⁵⁾
Average Radio RF power	10mW
Frequency band EMEA	1880 – 1900 MHz
Frequency band China ⁶⁾	1900 – 1920 MHz
Frequency band Latin America ⁶⁾	1910 – 1930 MHz
Frequency band North America ⁶⁾	1920 – 1930 MHz
<p>5) The transmitted Radio RF power is according to local regulations</p> <p>6) The I766 handset has a triple frequency band and can be used in the EMEA, American and Chinese DECT frequency band</p>	

Environmental Conditions

Temperature range	<ul style="list-style-type: none"> Operating: -10°C to +55°C Transport: -40°C to +70°C Storage: -15°C to +55°C
Relative Humidity	<ul style="list-style-type: none"> Operating: 10 to 95% Transport: 10 to 100% Storage: 10 to 95%

Package content

I766 with spring belt clip
Pull cord
Lithium-ion battery pack (1100 mA)

Compliance

The I766 handset carries a CE mark (European directive 1999/5/EC)	
EMC	EN 301 489-1, EN 301 489-6, EN 301 489-17
EMF	EN 50360
RF DECT	EN 301 406
RF Bluetooth	EN 300 328
Safety	EN 60950-1:2006 + Amendments
SAR	EN 62209-1, EN 62209-2
Integrated Bluetooth	Bluetooth protocol 3.0+ EDR + 4.0 (BLE) Headset profile (HSP) 1.2 Handsfree profile (HFP) 1.6

Compatibility

Platform Compatibility IP DECT	<ul style="list-style-type: none"> • Aspire, IPC500, SV8100 and SV9100 • 2000IPS, SV8300 and SV9300 • SV7000, SV8500 and SV9500 • iS3000 with DECT or IP DECT • SIP@Net • XN120, IPC100, SV8100 and SV9100 • Certified SIP enabled PBXs or SIP servers • Certified systems of Alcatel Lucent, Cisco and Broadsoft
---	---

Directives and regulation

European Union	<ul style="list-style-type: none"> • R&TTE directive 1999/5/EC • EMC directive 2004/108/EC • LVD directive 2006/95/EC • ROHS directive 2011/65/EU • WEEE directive 2012/19/EU • ERP directive 2009/125/EC
USA and Canada	<ul style="list-style-type: none"> • FCC part 15C, 15D • RSS 210, RSS 213 • HAC/VC

Access Point



10-074-02 July, 15 © 2015 NEC Corporation. All rights reserved. NEC and the NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All trademarks identified with © or TM are registered trademarks or trademarks of their respective owners. Models may vary for each country, and due to continuous improvements this specification is subject to change without notice. Please refer to your local NEC representative(s) for further details.

About NEC Corporation: NEC Corporation is one of the world's leading providers of Internet, broadband network and enterprise business solutions dedicated to meeting the specialized needs of its diverse and global base of customers. NEC delivers tailored solutions in the key fields of computer, networking and electron devices, by integrating its technical strengths in IT and Networks. The NEC Group employs more than 150,000 people worldwide. For additional information, please visit the NEC home page at: <http://www.nec.com>

For further information please contact your local NEC representative or:

North America (USA)
NEC Corporation of America
www.necam.com

South Asia (Singapore)
NEC Asia Pacific
www.nec.com.sg

Corporate Headquarters (Japan)
NEC Corporation
www.nec.com

Oceania (Australia)
NEC Australia Pte Ltd
www.nec.com.au

EMEA (Europe, Middle East, Africa)
NEC Enterprise Solutions
www.nec-enterprise.com