

# DH-PFS3016-16GT-M

## Ethernet Switch



- Fast forwarding: All ports can run at their highest speed at the same time, with no pressure running in concurrent flow scenarios.
- Plug and play: Just power-on and enjoy your device. No configuration required. It is suitable for forwarding scenarios.
- Fanless design: A fanless design is used to effectively reduce noise and create a quiet, serene environment. Its design also reduces mechanical loss to a certain extent and increases service life.
- Flexible installation: Supports multiple installation methods such as desktop mount and wall mount. Suitable for various installation scenarios.



### System Overview

The Device is a layer-2 commercial switch. It has a high-performance switching engine and a large buffer memory to ensure smooth video stream transmission. With a full-metal and fanless design, the Device features great heat dissipation capability on the shell surface. The Device is an unmanaged switch, so it does not need to be configured through web interface, which simplifies installation.

### Functions

#### Plug and Play

No configuration is required. Suitable for terminal connection.

#### Fanless Design

The fanless design reduces noise, enhances user experience, reduces mechanical losses and improves service life to a certain extent.

#### Easy Installation

Supports desktop, rack mounting, wall mounting and DIN-rail mounting, suitable for various scenarios.

### Scene

The Device is applicable for use in a variety of scenarios, such as in the home and office, on server farms, and in small malls.

## Technical Specification

### Hardware

|                               |   |
|-------------------------------|---|
| Power Adapter Provided        | Yes                                     |
| PoE                           | Not supported                           |
| Ethernet Port                 | 16                                      |
| Ethernet Port Speed           | 10/100/1000 Mbps                        |
| Ethernet Port Uplink Speed    | 10/100/1000 Mbps                        |
| Description of Function Slots | Port 1-16: 16 × RJ-45, 10/100/1000 Mbps |
| Power Supply                  | 12 VDC external power supply            |
| Operating Temperature         | -10 °C to +55 °C (+14 °F to +131 °F)    |
| Operating Humidity            | 5%–95% (RH)                             |
| Storage Temperature           | -40 °C to +85 °C (-40 °F to +185 °F)    |
| Storage Humidity              | 5%–95% (RH)                             |

### Performance

|                        |  |
|------------------------|--|
| Layer                  | Layer 2  |
| Management Type        | No   |
| Switching Capacity     | 32 Gbps  |
| Packet Forwarding Rate | 23.68 Mpps   |
| Packet Buffer Size     | 2 Mbit   |
| Jumbo Frame            | 10K Byte   |
| MAC Table Size         | 8K   |
| Communication Standard | IEEE 802.3; IEEE 802.3u; IEEE 802.3x; IEEE 802.3ab |

### General

|                     |   |
|---------------------|---|
| Statics Protection  | Air discharge: 8 kV Contact discharge: 6 kV     |
| Lighting Protection | Common mode: 2 kV Differential mode: 1 kV       |
| Product Dimensions  | 235 mm × 103 mm × 27 mm (9.25" × 4.06" × 1.06") |
| Casing              | Metal   |
| Installation        | Desktop mount; wall mount                       |

## Dimensions (mm[inch])

